

MK GRANITE GLEAM™

MK GRANITE GLEAM™

MK Granite Gleam™ is a non-wax compound for the polishing of worn granite floor areas. MK Granite Gleam™ contains only high-quality abrasives. MK Granite Gleam™ does not replace diamond grinding of granite surfaces; it is used as part of a non-wax maintenance polishing system for granite surfaces and high polishing after diamond refinishing has been completed.

TO APPLY MK GRANITE GLEAM™ YOU WILL NEED:

1. MK Granite Gleam™.
2. Floor Buffer (175 to 350 RPM). Water tank and splash guard are optional.
3. Natural hair pad.

DIRECTIONS:

Note: If the stone surface has wax or sealer to be removed, use MK Strip Klean™, following directions on container.

1. Cover baseboards, carpet, etc. with protective plastic and/or tape.
2. Wet marble surface. Sprinkle MK Granite Gleam™ on the floor space (2oz./10 sq. ft.) over an area no larger than 25 sq. ft. at a time.
3. Make a slurry with the MK Granite Gleam™ and water mixture. Buff this mixture with a natural hair pad for about 15 minutes per 25 sq. ft.
4. Check the level of gloss with a squeegee. When the desired level of gloss is achieved, squeegee the MK Granite Gleam™ mixture to adjacent area and repeat the process. Add MK Granite Gleam™ as needed.
5. Vacuum dry the MK Granite Gleam™ mixture. Wet the polished area and buff again with same pad without adding more MK Granite Gleam™.
6. Vacuum dry, damp mop with MK Neutral Klean™ solution and let dry.
7. Buff the polished area with a white pad.

NOTE: If needed, repeat above procedures until desired results are achieved.

COVERAGE: Up to 150 sq. ft. per lb.

Marble Kare Products, Inc. will not be liable for any damage ensuing to property or injury to operator or other person due to the misuse or misapplication of MK Granite Gleam™ or any other chemical sold by them. **Store in a dry place.** For further technical specification, see Material Safety Data Sheet.